

UltraPatch WetFix

ULTRATITE
SOLUTIONS



Features and Benefits

- Industry leading plasticizer free urethane/silicone hybrid formulation
- Self-Leveling technology for all seams, fasteners, ridge caps, flashings, and penetrations.
- Moisture Curing multi-purpose one-component paintable sealant/adhesive.
- Adheres to all silicones
- Designed for Industrial uses requiring elasticity, high strength, and excellent adhesion.
- May be applied to surfaces at or below freezing temperatures. Make all attempts to remove frost.
- Performance at temperatures as low as -40 degrees F.
- **Bonds to damp surfaces and can be applied in the rain.**
- Cures to a Waterproof tough flexible sealant.
- Low odor and minimal shrinkage.
- Non-staining and mildew resistant.
- UV resistant.
- VOC Compliant

Colors: White

Installation

Can be applied to most surfaces without primer. Brush or roller apply.

It can be used in wet conditions and even while raining.

Review Ultra Tite Solutions' specifications and details for complete installation information. Please contact UTS for more information.

Recommended Uses

Industrial uses requiring high elasticity, high strength, and outstanding adhesion for a wide range of substrates. GreenPatch Wet Fix bonds aggressively to PVC, aged TPO, metal, steel, aluminum, ceramics, spray foam, Styrofoam, EPS, glass, wood, fiberglass, concrete, bituminous and modified bituminous materials, silicone, and coated metals. Contact your local sales representative for specific applications. Always perform a pull test to ensure proper adhesion

Typical Physical Properties

Property	Result
Tensile Strength	200 PSI
Elongation at break	500%
Hardness Shore A	25 (5-day ambient cure)
Slump	Zero slump
Application Temp	13 to 200 degrees F
Low Flex Temp	-20 Degrees F
Service Temp	-40 to 200 Degrees F

Typical properties and characteristics are based on samples tested and are not guaranteed for all samples of this product. This data and information is intended as a guide and does not reflect the specification range for any particular property of this product.

Shipping Information

Size	Class
2-gallon pail (7.57 L) 22.4 lbs. per pail	55

D.O.T. Classification: Roof Coating, Non-Regulated Protect from freezing (32°F/0°C) during shipping and storage

403 Century Plaza Dr. Ste 400, Houston, TX 77073

832-827-2925

www.ultratite.com

